

P4-10200 series

Properties

One side machine coated, white paper with semi-gloss appearance. The adhesive features excellent tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Particularly good performance at lower temperatures.

Table 1. Face stock technical data

Not for specification purposes

Face Stock Technical Data	
Material	Paper
Color	White
Appearance	Semi gloss
Caliper	69 µm
Adhesive	Rubber based

Table 2. Adhesive technical data

Not for specification purposes

Adhesive technical data			
Initial Tack	720	N/m	FTM 9 glass
Peel Adhes. 90° (after 24 hours)	360	N/m	FTM 2 stainless steel
Minimal Application Temperature	-5°C		
Service Temperature	-40°C to +70°C		

Table 3. Ribbon technical data

Not for specification purposes

Ribbon technical data	
Type	Blend
Color	Black
Film thickness	3,0 µm
Total ribbon thickness	7,2 µm
Recommended maximum print speed	250 mm/s

Shelf Life

24 months from date of manufacture of product when properly stored at 22°C and 50% relative humidity.

Special Considerations:

For maximum bond strength, the surface should be clean and dry. Typical cleaning solvents are heptane and isopropyl alcohol.

Note:

Information presented have been determined by standard test methods and are values not to be used for specification purposes. Our recommendations on the use of our products are based on tests but we would ask for conducting your own tests to determine their suitability for your applications. Citizen cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

Application ideas

PALLET PACK
GS1 labels and ODETTE labels;
pallets and bulks

Examples

P4-10208
P4-10209
P4-10210