

P4-11301

Properties

White destructible vinyl offers excellent destructibility on a broad range of substrates. It has very good dimensional stability combined with high solvent and UV resistance and is designed to accept thermal transfer print process. Permanent acrylic adhesive exhibits low ooze combined with excellent adhesion on a broad range of surfaces. Typical application: tamper evident security labels.

Table 1. Face stock technical data

Not for specification purposes

Face Stock Technical Data	
Material	Vinyl PVC
Color	White
Appearance	Matt
Caliper	50µm
Adhesive	Acrylic

Table 2. Adhesive technical data

Not for specification purposes

Adhesive Technical Data	
Minimal Application Temperature	5°C
Service Temperature	-30°C to +80°C

Table 3. Ribbon technical data

Not for specification purposes

Ribbon technical data	
Type	Resin
Color	Black
Film thickness	4,5 µm
Total ribbon thickness	6,2 µm
Recommended maximum print speed	150 mm/s

Shelf Life

24 months from date of manufacture of product when properly stored at 22°C and 50% relative humidity.

Special Considerations

For maximum bond strength, the surface should be clean and dry. Typical cleaning solvents are heptane and isopropyl alcohol.

Note

Information presented have been determined by standard test methods and are values not to be used for specification purposes. Our recommendations on the use of our products are based on tests but we would ask for conducting your own tests to determine their suitability for your applications. Citizen cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

Application ideas

INVENT PACK
permanent marking of fixed
assets for inventory

Examples

P4-11301